

999.00 EUR

 incl. 19% VAT, plus [shipping](#)

- SATA !

Features :

- BD-RE/-R (SL) 4X Speed Writing/Reading
- BD-RE/-R (DL) 2X Speed Writing/Reading
- BD-ROM (SL/DL) 4X Speed Reading
- DVD Multi Read/Write support

| Compatible Media/Maximum Transfer Rate | | | |
|--|--------------|-------|------|
| Media | | Write | Read |
| BD-RE | Single Layer | 2X | 2X |
| | Dual Layer | 2X | 2X |
| BD-R | Single Layer | 4X | 4X |
| | Dual Layer | 2X | 2X |
| BD-ROM (Single Layer/Dual Layer) | | - | 4X |
| DVD-RAM | | 5X | 5X |
| DVD-R | | 8X | 8X |
| DVD-R DL (Dual Layer) | | 4X | 4X |
| DVD-RW | | 6X | 6X |
| DVD+R | | 8X | 8X |
| DVD+R DL (Double Layer) | | 4x | 4X |
| DVD+RW | | 8X | 8X |
| DVD-ROM | Single Layer | - | 8X |
| | Dual Layer | - | 8X |
| CD-R | | 24X | 24X |
| CD-RW | | 16X | 24X |
| CD-ROM | | - | 24X |

| Specifications | | |
|--------------------------------------|-----------------|--|
| Loading Type | | 12.7mm Height Tray Loading |
| Data Capacity (Blu-ray Disc SL/DL) | | 25 / 50Gbytes |
| Interface | | Slimline SATA |
| Buffer Memory | | 8Mbytes |
| Error Rate | Soft Read Error | Less than 10 ⁻⁹ |
| | Hard Read Error | Less than 10 ⁻¹² |
| Power Requirements (Voltage) | | DC +5V ±0.25V |
| Temperature (Center of Top Cover) | Operating | 5°C ■ 50°C |
| | Storage | -30°C ■ 65°C |
| Relative Humidity | Operating | 5% ■ 90% (Non-condensing) |
| | Storage | 5% ■ 95% (Non-condensing) |
| Dimensions | | 128.0(W) × 12.7(H) × 129.0(D) mm (Depth dimension includes Bezel) |