

209.00 EUR  
incl. 19% VAT, plus [shipping](#)



**Support:**  [Specifications](#)

|                                         |                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chip                                    | Marvell                                                                                                                                                                                                                                                                                                                                                                          |
| Dimensions                              | 150x100x36mm                                                                                                                                                                                                                                                                                                                                                                     |
| Certifications&Safety                   | CE, FCC, ROHS                                                                                                                                                                                                                                                                                                                                                                    |
| I/O Ports                               | 5x 10/100/1000BaseT(X)                                                                                                                                                                                                                                                                                                                                                           |
| Management                              | LED: Power, port connection<br>No                                                                                                                                                                                                                                                                                                                                                |
| Standards                               | IEEE802.3 10Base-T Ethernet standard<br>IEEE802.3u 100Base-TX/FX<br>IEEE802.3x 1000Base-X<br>IEEE802.3ab 1000Base-T(X)<br>IEEE802.3x Flow control<br>10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m)<br>100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m)<br>1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m) |
| Network interface / Wire specifications |                                                                                                                                                                                                                                                                                                                                                                                  |
| PoE Support                             | No                                                                                                                                                                                                                                                                                                                                                                               |
| Power input / consumption               | Input voltage 12-36VDC<br>Reverse connection protection<br>Power interface : 5pin terminal                                                                                                                                                                                                                                                                                       |
| Operating temperature                   | -40~85°C                                                                                                                                                                                                                                                                                                                                                                         |
| Cooling                                 | Fanless                                                                                                                                                                                                                                                                                                                                                                          |
| MTBF                                    | 100.000hrs                                                                                                                                                                                                                                                                                                                                                                       |