

539.00 EUR  
incl. 19% VAT, plus [shipping](#)



- LGA1151 !
- H310 Chipset !
- 19" Enclosure !

- Intel® 8th & 9th Core i3/i5/i7/Pentium Processor
- Support 2\* DDR4 2666 SO-DIMM up to 32 GB
- 4\* USB3.1, 2\* USB2.0, 2\* COM, 1\* HDMI , 1\* DP, 2\* RJ45, Line-out/Line-in/MIC
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

|                |  |                      |  |
|----------------|--|----------------------|--|
| Dimensions     | – 330 (W) x 192 (D) x 44 (H) mm  |                      |  |
| MB model       | – MI98-00 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)  |                      |  |
| Part No        | Non-Wifi   | Wifi                 |  |
|                | – HBJC150I98-H310-B  | – HBJC150I98W-H310-B |  |
| CPU            | – Intel® 8/9th Core i3/i5/i7/Pentium/Celeron LGA Processor (TDP: 95W)  |                      |  |
| BIOS           | – AMI Flash ROM  |                      |  |
| Memory         | – 2* Dual CH non-ECC DDR4 2666 MHz SDRAM SO-DIMM up to 32GB  |                      |  |
| Network        | – 2* GbE (1*Intel i219V, 1* Realtek 8111H)   |                      |  |
| Storage        | – 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay<br>– 1 *M.2_SSD (M key-2242/2280) support NVMe   |                      |  |
| Expansion      | – 1* M.2 E-key 2230 (PCIex1/USB2.0)<br>– Support onboard TPM2.0 (MI98-02) / optional   |                      |  |
| Rear I/O Port  | – 4 * USB 3.1 (Gen. 1)<br>– 1 * HDMI (Max Resolution: 4096x2160@30Hz)<br>– 1 * DP (Max Resolution: 4096x2304@60Hz)<br>– 2 * RJ45 (1*Intel i219V, 1* Realtek 8111H)<br>– 1 * Mic , 1 * Line in , 1 * Line-out<br>– 2 * COM (COM 1 support RS232/422/485)<br>– AC-in |                      |  |
| Front I/O Port | – 1 * Power button<br>– 1 * Reset button<br>– 1 * Power LED<br>– 1 * HDD LED<br>– 2 * USB 2.0  |                      |  |
| Power Source   | – 1U 250W FLEX POWER<br>– AC 90~240V input   |                      |  |

|               |   |
|---------------|---|
| Certification | – CE, FCC, LVD, RoHS  |
| Environment   | – Operating Temperature : 0°C~50°C<br>– Storage Temperature : -10°C~70°C<br>– Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Packing       | – Net Weight■3.5 KG<br>– Gross Weight■4.5 KG<br>– Color Box Dimension■560(W) x 400(D) x 140(H) mm                           |