



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- For Celeron-M/Pentium-M
- Integr. Automotive PSU
- PCMCIA

CARTFT.COM

Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

As an additional highlight this barebone offers a PCMCIA slot.

CALU specifications	
<b>Processor (supported)</b>	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
<b>Memory</b>	Supports DDR 400/333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
<b>Video</b>	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
<b>Audio</b>	Software AC '97 Audio CODEC
<b>Peripheral Connection</b>	Front : 1 x PCMCIA Slot 1 x IEEE 1394 Firewire port 1 x MIC Port 1 x Ear Phone output Jack Power-on button Reset button Power-on and HDD LED  Rear : 1 x RS232 COM port 1 x parallel printer port 1 x RJ45 10/100Mb Fast Ethernet 1 x Line-Out output Jack 2 x USB 2.0 / 1.1 Ports 1 x 15 pin VGA 1 x DVI
<b>Storage</b>	One 2.5 inch Hard Disk and 9.5mm high. (Support Ultra DMA 33/66/100).
<b>Weight &amp; Size</b>	System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm
<b>Power req.</b>	9-16V, 5A

**Accessory**

**Storage** Supports all 2.5" standard IDE hard drive, ATA-100/66/33.

**Scope of supply** Connector cable for Plus, ignition plus and ground

Barebone

CPU Kühkörper

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)